

PRODUCT CODE
WE310

APRIL 2020



Material: Manufactured from 1.5mm thick grade 304 stainless steel with a satin polish finish.

Length: The wash troughs are held in stock and available to order in four standard lengths: 1000mm, 1500mm, 2000mm, and 2500mm long.

Fixing: The stock wash troughs are supplied with integral wall fixing points at each end. The integral rear flange is pierced for screw fixing along the top edge. Optional stainless steel front support legs are available to order.

Waste Outlet: Supplied with a centre 38mm BSP unslotted flush grated waste fitting (no plug or overflow).

Dimensions: 400mm front to back. 150mm deep with 25mm high rear flange.

Tap Holes: The wash troughs are pre-drilled with a single 35mm tap holes per user: 1000mm - 2 single tap holes. 1500mm - 3 single tap holes. 2000mm - 4 single tap holes. 2500mm - 5 single tap holes.

Optional Extras: Stainless steel front support legs. Taps and plastic or chrome plated brass bottle traps.

Specification

| | |
|----------------------------|--|
| Material | Grade 304 stainless steel, 1.5mm thick |
| Lengths and weights | 1000mm 1500mm 2000mm 2500mm 12kg 17kg 22kg 37kg |
| Height | 150mm bowl 25mm upstand |
| Front to back | 400mm |
| Tap ledge | 70mm |
| Tap holes | 1000mm: 2 single 35mm 1500mm: 3 single 35mm 2000mm: 4 single 35mm 2500mm: 5 single 35mm |
| Waste | Centre 38mm flush grated waste fitting (no plug or overflow) |
| Fixing | Integral wall mounting points |
| Options | Front support legs, 950mm high Plastic or chrome plated brass bottle traps Waste fitting with overflow Taps from our extensive range Powder coated colour finish, extra 7 to 10 working days |

