

WALL MOUNTED DRINKING FOUNTAIN

PRODUCT CODE
CWS WMDF 462

MAY 2016



Special Features

- WRAS APPROVED BUBBLER VALVE
- HYGIENIC AND VANDAL RESISTANT
- SMOOTH RADIUSED DESIGN
- INTEGRAL SPLASHBACK
- EASILY INSTALLED AT ADULT OR JUNIOR HEIGHT
- UNDERSHROUD TO CONCEAL PIPEWORK
- OPTIONAL Enviro-Glaze COLOUR FINISHES

Description

The wall mounted drinking fountain is hygienic, robust and easily installed at adult or junior height. The WRAS approved shielded bubbler valve is positioned for ease of use and the smooth radiused design eliminates sharp corners which can cause injury. The drinking fountain is formed with a deep undershroud to conceal the waste fitting and incorporates integral wall mounting brackets.

Construction

The drinking fountain is manufactured in one piece without joints or crevices from grade 304 stainless steel polished to a satin finish. For ease of cleaning and hygiene a splashback is incorporated in the top of the drinking fountain. The integral half height undershroud incorporates a removable access panel, in the base, held in position by security type screws. The drinking fountain is supplied with a flush grated waste fitting and a WRAS approved chrome plated shielded bubbler complete with a self closing push button valve.

Option

A range of Enviro-Glaze colour finishes including white

This drinking fountain is available in a BOTILE FILLER version - please refer to model 464

Order Codes and Technical Specification

Please refer to the Technical Specification Sheet



Unit 1, Elphicks Farm, Spelmonden Road, Horsmonden, Tonbridge. Kent TN12 8EL
Phone: 01580 211648 E-mail: info@cactuswatersystems.co.uk